

2360

PLANT MIXED ASPHALT PAVEMENT Combined 2360/2350 (Gyratory/Marshall Design) Specification

For 2003 Construction Season

1. DESCRIPTION	1
A. MIXTURE DESIGNATIONS	1
B. MINIMUM LIFT THICKNESS	2
2. MATERIALS	2
A. AGGREGATE	2
A1. GENERAL	2
A2. CLASSIFICATION	3
A3. RECYCLED ASPHALTIC PAVEMENT MATERIALS (RAP)	4
B. MANUFACTURED CRUSHED FINES	4
C. QUALITY REQUIREMENTS	4
C1. LOS ANGELES RATTLER (LAR)	4
C2. MAGNESIUM SULFATE SOUNDNESS	5
C3. SPALL MATERIALS AND LUMPS	5
C4. INSOLUBLE RESIDUE	5
D. AGGREGATE RESTRICTIONS	5
E. GRADATION REQUIREMENT	5
F. ADDITIVES	6
G. ASPHALT BINDER MATERIAL	6
G1. ASPHALT BINDER SELECTION CRITERIA FOR RAP MIXES	7
3. MIXTURE DESIGN	7
A. MIXTURE DESIGN GENERAL	7
B. LABORATORY MIXTURE DESIGN (OPTION 1)	8
B1. AGGREGATE SAMPLE	8
B2. MIXTURE SAMPLE	8
B2a. MIXTURE AGGREGATE REQUIREMENTS	8
B2b. MIXTURE REQUIREMENTS	9
B2c. VMA CRITERIA	10
B3. TENSILE STRENGTH RATIO SAMPLE	11
B4. AGGREGATE SPECIFIC GRAVITY	11
C. DOCUMENTATION	11
D. MODIFIED MIXTURE DESIGN (OPTION 2)	13
D1. MIXTURE SAMPLE	13
D2. INITIAL PRODUCTION TEST VERIFICATION	13
D3. TENSILE STRENGTH RATIO SAMPLE	14
D4. MARSHALL STABILITY (MARSHALL DESIGN ONLY)	14
E. MIXTURE DESIGN REPORT	14

4. MIXTURE QUALITY MANAGEMENT (QUALITY CONTROL/QUALITY ASSURANCE)	14
A. QUALITY CONTROL (QC)	14
A1. CONTRACTOR CERTIFIED PLANT HMA	15
A1a. CERTIFICATION PROCEDURE	15
A1b. MAINTAINING CERTIFICATION	15
A1c. REVOCATION OF PLANT CERTIFICATION	15
B. QUALITY ASSURANCE (QA)	15
C. CONTRACTOR'S QUALITY CONTROL	16
C1. PERSONNEL REQUIREMENTS	16
C2. LABORATORY REQUIREMENTS	16
D. SAMPLING AND TESTING	16
E. PRODUCTION TESTS	17
E1. ASPHALT BINDER CONTENT, PERCENT"	17
E2. MARSHALL BULK SPECIFIC GRAVITY (Gmb)	18
E2a. GYRATORY BULK SPECIFIC GRAVITY (Gmb)	18
E3. MAXIMUM SPECIFIC GRAVITY (Gmm)	18
E4. AIR VOIDS-INDIVIDUAL & ISOLATED	18
E5. VOIDS IN MINERAL AGGREGATE (VMA)	18
E6. GRADATION-BLENDED AGGREGATE	19
E7. COARSE AGGREGATE ANGULARITY (CAA)	19
E8. FINE AGGREGATE ANGULARITY (FAA)	19
E8a. -#4 MANUFACTURED CRUSHED FINES	19
E9. FIELD TENSILE STRENGTH RATIO (TSR)	19
E10. AGGREGATE SPECIFIC GRAVITY (Gsb)	21
E11. MOISTURE CONTENT	21
E12. ASPHALT BINDER SAMPLES	21
F. DOCUMENTATION (RECORDS)	21
G. DOCUMENTATION (CONTROL CHARTS)	22
H. JMF LIMITS	23
I. JMF BANDS	23
J. JMF ADJUSTMENT	23
J1. JMF ADJUSTMENT FOR PROPORTION CHANGE >10%	24
K. CORRECTIVE ACTION-% Asphalt Binder Content, VMA, Gradation and Production Air Voids	24
L. FAILING MATERIALS	24
L1. ISOLATED FAILURE AT MIXTURE START-UP Production Air Voids	25
L1a. INDIVIDUAL FAILURE AT MIXTURE START-UP - VMA	25
L1b. INDIVIDUAL FAILURE -	25
(Gradation, Percent Asphalt Binder, Production Air Voids & VMA)	
L2. MOVING AVERAGE FAILURE AT MIXTURE START-UP Production Air Voids	26
L2a. MOVING AVERAGE FAILURE AT MIXTURE STARTUP-VMA	26
L2b. MOVING AVERAGE FAILURE-PRODUCTION AIR VOIDS	26
L2c. MOVING AVERAGE FAILURE -	27
Percent Asphalt Binder Content, VMA & Gradation	
L3. COARSE & FINE AGGREGATE CRUSHING FAILURE	27
M. QUALITY ASSURANCE	27
TABLE 2360.4-M ALLOWABLE TOLERANCES BETWEEN TESTS	28
N. VERIFICATION TESTING	28

5. CONSTRUCTION REQUIREMENTS	29
A. GENERAL	29
B. RESTRICTIONS	29
C. EQUIPMENT	30
C1. ASPHALT MIXING PLANTS	30
C2. PLACEMENT AND HAULING EQUIPMENT	31
D. TREATMENT OF THE SURFACE - TACK COAT	32
E. COMPACTION OPERATIONS	32
F. CONSTRUCTION JOINTS-TRANSVERSE & LONGITUDINAL	33
G. ASPHALT MIXTURE PRODUCTION (FOB DEPT. TRUCKS)	33
H. SMALL QUANTITY HMA PAVING	33
6. PAVEMENT DENSITY	34
A. GENERAL	34
B. MAXIMUM DENSITY METHOD	34
B1. MAXIMUM DENSITY DETERMINATION	34
B2. REQUIRED DENSITY	34
B2a. LOTS AND CORE LOCATIONS	35
B3. CORE TESTING	36
B4. BLANK	36
B5. MAXIMUM DENSITY ACCEPTANCE & PAYMENT SCHEDULE	36
C. ORDINARY COMPACTION METHOD	38
C1. ROLLERS	39
C2. STEEL-WHEELED ROLLERS	39
C3. PNEUMATIC-TIRED ROLLERS	39
C4. TRENCH ROLLERS	39
C5. MIXTURE TEMPERATURE CONTROLS	40
7. THICKNESS AND SURFACE SMOOTHNESS REQUIREMENTS	40
A. THICKNESS	40
B. SURFACE REQUIREMENTS	40
C. PAVEMENT SMOOTHNESS	41
C1. GENERAL-SMOOTHNESS REQUIREMENTS	41
C2. MEASUREMENT	42
C3. PROFILOGRAPH TESTING	42
C4. PROFILE INDEX	43
C5. SURFACE CORRECTIONS	43
C6. PAYMENT	44
8. METHOD OF MEASUREMENT	46
A. ASPHALT MIXTURE	46
B. BLANK	46
C. ASPHALT MIXTURES MEASURED BY THE SQUARE METER [SQUARE YARD] PER SPECIFIED (mm[INCH]) AND FOR MIXTURES MEASURED BY THE [SQUARE YARD INCH]	46