

(2360) PLANT MIXED ASPHALT PAVEMENT Combined 2360/2350 (Gyratory/Marshall Design) Specification

For 2004 Construction Season

1. DESCRIPTION	1
A. MIXTURE DESIGNATIONS	1
B. MINIMUM LIFT THICKNESS	2
2. MATERIALS	2
A. AGGREGATE	2
A1. GENERAL	2
A2. CLASSIFICATION	3
A3. RECYCLED ASPHALTIC PAVEMENT MATERIALS (RAP)	4
B. MANUFACTURED CRUSHED FINES (--4 MATERIAL)	4
C. QUALITY REQUIREMENTS	5
C1. LOS ANGELES RATTLER	5
C2. MAGNESIUM SULFATE SOUNDNESS	5
C3. SPALL MATERIALS AND LUMPS	5
C4. INSOLUBLE RESIDUE	5
D. AGGREGATE RESTRICTIONS	5
E. GRADATION REQUIREMENT	5
F. ADDITIVES	6
G. ASPHALT BINDER MATERIAL	7
G1. ASPHALT BINDER SELECTION CRITERIA-RAP MIXES- <u>TABLE</u>	8
3. MIXTURE DESIGN	8
A. MIXTURE DESIGN GENERAL	8
B. LABORATORY MIXTURE DESIGN (OPTION 1)	9
B1. AGGREGATE SAMPLE	9
B2. MIXTURE SAMPLE- <u>TABLE</u>	9
B2a. MIXTURE AGGREGATE REQUIREMENTS	9
B2b. MIXTURE REQUIREMENTS	10
B2c. VMA CRITERIA	11
B3. TENSILE STRENGTH RATIO SAMPLE	12
B4. AGGREGATE SPECIFIC GRAVITY	12
C. DOCUMENTATION	12
D. MODIFIED MIXTURE DESIGN (OPTION 2)	14
D1. JMF SUBMITTAL	14
D2. INITIAL PRODUCTION TEST VERIFICATION	15
D3. TENSILE STRENGTH RATION SAMPLE	15
D4. MARSHALL STABILITY (MARSHALL DESIGN ONLY)	15
E. MIXTURE DESIGN REPORT	15
4. MIXTURE QUALITY MANAGEMENT (QA/QC)	16
A. QUALITY CONTROL (QC)	16
A1. CONTRACTOR CERTIFIED PLANT HMA	16
B. QUALITY ASSURANCE (QA)	16
C. CONTRACTOR'S QUALITY CONTROL	17
C1. PERSONNEL REQUIREMENTS	17
C2. LABORATORY REQUIREMENTS	17
D. SAMPLING AND TESTING - <u>TABLE</u>	17
E. PRODUCTION TESTS - <u>TABLE</u>	18
E1. ASPHALT BINDER CONTENT, PERCENT	19
E2. MARSHALL BULK SPECIFIC GRAVITY, Gmb (3 SPEC)	19
E2a. GYRATORY BULK SPECIFIC GRAVITY, Gmb (2 SPEC)	19
E3. MAXIMUM SPECIFIC GRAVITY, Gmm	19
E4. AIR VOIDS-INDIVIDUAL & ISOLATED(CALCULATION)	19

E5. VOIDS IN MINERAL AGGREGATE (VMA) CALCULATION	20
E6. GRADATION-BLENDED AGGREGATE	20
E7. COARSE AGGREGATE ANGULARITY	20
E8. FINE AGGREGATE ANGULARITY (FAA)	20
E8a. -#4 MANUFACTURED CRUSHED FINES	21
E9. FIELD TENSILE STRENGTH RATIO (TSR) - <u>TABLE</u>	21
E10. AGGREGATE SPECIFIC GRAVITY (Gsb)	22
E11. MOISTURE CONTENT	22
E12. ASPHALT BINDER SAMPLES	23
F. DOCUMENTATION (RECORDS)	23
G. DOCUMENTATION (CONTROL CHARTS)	24
H. JMF LIMITS - <u>TABLE</u>	24
I. JMF BANDS	25
J. JMF ADJUSTMENT	25
J1. JMF ADJUSTMENT FOR PROPORTION CHANGE >10%	26
K. CORRECTIVE ACTION-% Asphalt Binder Content, VMA, Gradation and Production Air Voids	26
L. FAILING MATERIALS	26
L1. ISOLATED FAILURE AT MIXTURE START-UP Production Air Voids	27
L2. INDIVIDUAL FAILURE AT MIXTURE START-UP - VMA	27
L3. INDIVIDUAL FAILURE - Gradation, % Asphalt Binader, Prod ir Voids and VMA	27
L4. MOVING AVERAGE FAILURE AT MIXTURE START-UP-Production Air Voids	28
L5. MOVING AVERAGE FAILURE AT MIXTURE START-UP-VMA	28
L6. MOVING AVERAGE FAILURE - Production Air Voids	28
L7. MOVING AVERAGE FAILURE - Percent Asphalt Binder, VMA, & Gradation	29
L8. COARSE AND FINE AGGREGATE CRUSHING FAILURE	29
M. QUALITY ASSURANCE	29
<u>TABLE 2360.4-M ALLOWABLE TOLERANCES BETWEEN TESTS</u>	30
N. VERIFICATION TESTING	30
5. CONSTRUCTION REQUIREMENTS	31
A. GENERAL	31
B. RESTRICTIONS	31
C. EQUIPMENT	32
C1. ASPHALT MIXING PLANTS	32
C2. PLACEMENT AND HAULING EQUIPMENT	33
D. TREATMENT OF THE SURFACE	34
E. COMPACTION OPERATIONS	34
F. CONSTRUCTION JOINTS	35
G. ASPHALT MIXTURE PRODUCTION (FOB DEPT. TRUCKS)	35
H. SMALL QUANTITY HMA PAVING	35
6. PAVEMENT DENSITY	36
A. GENERAL	36
B. MAXIMUM DENSITY METHOD	36
C. ORDINARY COMPACTION METHOD	40
7. THICKNESS AND SURFACE SMOOTHNESS REQUIREMENTS	42
A. THICKNESS	42
B. SURFACE REQUIREMENTS	43
C. PAVEMENT SMOOTHNESS - <u>TABLE</u>	43
8. METHOD OF MEASUREMENT	48
A. ASPHALT MIXTURE	48
B. BLANK	48
C. SQUARE METER vs SQUARE YARD	48